

Image Enhancement Systems

Many auto-sound systems cannot ideally provide for a convenient ideal mounting position. In some cases the tweeters may need to be mounted well below ear level. In order to embellish the extreme top end and to lift the image (usually toward the windshield area) the Image Enhancement system can add a dash of "air" and space to enable the best overall special character.



There is a good reason to add a pair of image enhancement tweeters upfront connected to an attenuator control unit which is to improve the distribution of the highs and to fuse those highs into the overall sound. This image enhancement system will bring the highs and stereo image sound stage level to where the drivers head sits.

"Image Enhancement" Kits



TW-19/LP
19mm twtr



TW-20/LP
20mm twtr



TW-25/LP
25mm twtr



Dash surface mount



Dash cobra mount



A-Pillar flush mount



A-Pillar surface mount

The CDT "Image Enhancement" control unit is supplied pre-wired. **ALL CDT Audio crossovers are designed with a special image tweet circuit and terminal on the PCB.** The "image enhancement" tweeters come with both flush and surface mounts. The system comes in a box with all mounting hardware necessary and a detailed installation manual.

The "Image Enhancement" control unit allows level setting in the tweeter pair while maintaining the crossover response shape throughout the useable range. Here the range from full on to minus 10dB. is shown. This represent as much attenuation than you would ever want to use.

The system consist of:

- (2) dome high powered "image enhancement" tweeters
 - (2) surface mounts
 - (2) flush mounts
 - (1) high powered image enhancement level control unit
- (Tweeters are available in silk or metal domes talk to your dealer for details).

